

RG 59 B/U



Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type. Impedance 75 Ohm

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,6 Steel/copper, bare
Core Insulation	3,7 PE
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U_0/U : 0 /0
Nominal Volatage DC	U_0/U : 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C bis 70 °C
Operating Temperature moving	0 °C bis 0 °C

Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type. Impedance 75 Ohm

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,6 Steel/copper, bare
Core Insulation	3,7 PE
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U_0/U : 0 /0
Nominal Volatage DC	U_0/U : 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C to 70 °C
Operating Temperature moving	0 °C to 0 °C

Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.
03001004		RG x 59 B/U	black - black	52.0	6.2
03001024	halogenfrei	RG x 59 B/U	black - black	52.0	6.2
03001012		RG x 59 B/U "PE"	black - black	55.0	6.2
03001006		RG x 59 B/U DUO	black - black	105.0	