

RG 62 A/U



Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,65 Steel/copper, bare
Core Insulation	3,7 PE, hollow
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U ₀ /U: 0 /0
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C bis 70 °C
Operating Temperature moving	0 °C bis 0 °C

Application

Used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions. The varied mechanical, thermal and electronic properties of coaxial cables allow the use to GHz levels according to the cable type.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

US-Military specifications MIL-C-17

Construction

Inner Conductor	1 x 0,65 Steel/copper, bare
Core Insulation	3,7 PE, hollow
Overall Shielding	bare, copper braid
Outer Insulation Material	special polyvinylchlorid (PVC)

Technical Data

Nominal Voltage	U ₀ /U: 0 /0
Nominal Volatage DC	U ₀ /U: 0 /0
Bending Radius fixed (xD)	0
Operating Temperature solid	-20 °C to 70 °C
Operating Temperature moving	0 °C to 0 °C

Prod. Nr.	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
Prod. Nr.	Dimensions	Color	Weight (kg/km) approx.	Outer-Diameter (mm) approx.
03001007	RG x 62 A/U	black - black	55.0	6.2