

DataLine S/FTP 1000 Mhz Cat7



Application

The excellent high frequency characteristics of the data cable are much better than required in Category 7 and also meet system reserves about 900 MHz.

Standards

EN 50288-4-1 ; EN 50173 ; EN 50174-2 ;
ISO/IEC 11801 2. Ausgabe ; IEC 61156-5

Nominal Velocity of Propagation NVP nom. 79,0

Construction

Inner Conductor 0,57mm bare copper (AWG23/1)
Core Insulation SFS-PE foamed
Core Color wt-bl, wt-or, wt-gn, wt-br (IEC 708-1)
Stranding Elements 4 pairs twisted
Shielding pairs Al-Foil
Overall Shielding braid shield copper tinned
Outer Insulation Material FR-LSOH

Technical Data

Nominal Voltage	U ₀ /U: 125 /125 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	700 V
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	4
Operating Temperature solid	-20 °C bis 60 °C
Operating Temperature moving	0 °C bis 50 °C
Fire Classes	Dca

Application

The excellent high frequency characteristics of the data cable are much better than required in Category 7 and also meet system reserves about 900 MHz.

Standards

EN 50288-4-1 ; EN 50173 ; EN 50174-2 ;
ISO/IEC 11801 2. Ausgabe ; IEC 61156-5

Nominal Velocity of Propagation NVP nom. 79,0

Construction

Inner Conductor 0,57mm bare copper (AWG23/1)
Core Insulation SFS-PE foamed
Core Color wt-bl, wt-or, wt-gn, wt-br (IEC 708-1)
Stranding Elements 4 pairs twisted
Shielding pairs Al-Foil
Overall Shielding braid shield copper tinned
Outer Insulation Material FR-LSOH

Technical Data

Nominal Voltage	U ₀ /U: 125 /125 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	700 V
Bending Radius moved (xD)	8
Bending Radius fixed (xD)	4
Operating Temperature solid	-20 °C to 60 °C
Operating Temperature moving	0 °C to 50 °C
Fire Classes	Dca

Datenkabel Kategorie 5 - 7 Computer Cables



Prod. Nr. Prod. Nr.	Option Option	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.
03452007	7	2x(4x2 x AWG 23/1)	yellow - yellow	106.0	12.0
03452011	7	2x(4x2 x AWG 23/1)	orange - orange	106.0	12.0
03452006		4x2 x AWG 23/1	yellow - yellow	53.0	7.0
03452010		4x2 x AWG 23/1	orange - orange	53.0	7.0
03456006		4x2 x AWG 23/1	orange - orange	53.0	7.0

ACS Handels GmbH
Kabel - Leitungen - Zubehör
Bahnhofstraße 1, 4531 Kematen / Krems

Tel.: +43 7228 200 880
E-Mail: office@acs.at

Technische Änderungen und Druckfehler vorbehalten
Technical changes and printing errors reserved

Produktabbildungen sind Symbolfotos
Product images are symbolic photos

Copyright© ACS Handels GmbH