

NSGAFöu 1,8/3 kV



Application

This cable is suitable for track bound vehicles and trackless trolley buses as well as for installations in dry locations, in switchboards and distributors up to 1.000 V as a short circuit and earth fault proof cable.

For use in direct current operation (DC) : Uo/U: 2.7/5.4 kV

Standards

DIN VDE 0250 part 602, DIN EN 60811-100 VDE 0473-811-100:2012-12

The cable complies with:
REACH Regulation EC 1907/2006
RoHS Directive 2011/65/EU, (EU) 2015/863

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor	fine-stranded tinned copper acc. DIN VDE 0295 cl. 5 and IEC 60228 cl. 5
Core Insulation	EPR rubber
Outer Insulation Material	polychloroprene 5GM3 to DIN VDE 0207 Part 21
Constant Against	abrasion and oil resistant acc. to DIN VDE 0473 Teil 811-2-1, UV-and Ozon resistant

Application

This cable is suitable for track bound vehicles and trackless trolley buses as well as for installations in dry locations, in switchboards and distributors up to 1.000 V as a short circuit and earth fault proof cable.

For use in direct current operation (DC) : Uo/U: 2.7/5.4 kV

Standards

DIN VDE 0250 part 602, DIN EN 60811-100 VDE 0473-811-100:2012-12

The cable complies with:
REACH Regulation EC 1907/2006
RoHS Directive 2011/65/EU, (EU) 2015/863

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor	fine-stranded tinned copper acc. DIN VDE 0295 cl. 5 and IEC 60228 cl. 5
Core Insulation	EPR rubber
Outer Insulation Material	polychloroprene 5GM3 to DIN VDE 0207 Part 21
Constant Against	abrasion and oil resistant acc. to DIN VDE 0473 Teil 811-2-1, UV-and Ozon resistant

Technical Data

Nominal Voltage	U ₀ /U: 1800 /3000 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	6 kV
Bending Radius moved (xD)	10
Bending Radius fixed (xD)	6
Operating Temperature solid	-40 °C bis 90 °C
Operating Temperature moving	-25 °C bis 90 °C
Short Circuit Temperature	250 °C
Short Circuit Duration	5 sek.
Fire Classes	Eca

Technical Data

Nominal Voltage	U ₀ /U: 1800 /3000 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	6 kV
Bending Radius moved (xD)	10
Bending Radius fixed (xD)	6
Operating Temperature solid	-40 °C to 90 °C
Operating Temperature moving	-25 °C to 90 °C
Short Circuit Temperature	250 °C
Short Circuit Duration	5 sek.
Fire Classes	Eca

Prod. Nr. Prod. Nr.	Dimensions Dimensions	Color Color	Weight (kg/km) approx. Weight (kg/km) approx.	Outer-Diameter (mm) approx. Outer-Diameter (mm) approx.	Power Load Air (A) Power Load Air (A)
00407001	1 x 1,5	black - black	50.0	6.0	30
00407002	1 x 2,5	black - black	70.0	6.3	41
00407003	1 x 4	black - black	80.0	6.8	55
00407017	1 x 4	orange - orange	80.0	6.8	55
00407004	1 x 6	black - black	100.0	7.0	70
00407018	1 x 6	orange - orange	100.0	7.0	70
00407005	1 x 10	black - black	160.0	8.5	98
00407006	1 x 16	black - black	230.0	10.0	132
00407007	1 x 25	black - black	360.0	12.0	176
00407008	1 x 35	black - black	460.0	13.5	218
00407009	1 x 50	black - black	620.0	15.0	276
00407010	1 x 70	black - black	820.0	17.0	347
00407011	1 x 95	black - black	1,080.0	19.5	416
00407012	1 x 120	black - black	1,330.0	20.8	488
00407013	1 x 150	black - black	1,630.0	23.4	566
00407014	1 x 185	black - black	1,960.0	25.0	644
00407015	1 x 240	black - black	2,530.0	28.0	775
00407016	1 x 300	black - black	3,090.0	30.0	898
00407019	1 x 400	black - black	4,120.0	35.0	1060
00407020	1 x 500	black - black	5,500.0	38.0	1250