

## (N)HXH-J E30



### Anwendung

Überall dort, wo durch hohe Sachwertkonzentration im Brandfall Schaden an Mensch und Material verhindert werden muss. Geeignet zur festen Installation in trockenen, feuchten und nassen Räumen auf und unter Putz, sowie im Mauerwerk und im Beton. Sie sind auch für die Verlegung im Freien und Erdreich bei einer Verlegung in Rohren geeignet. Die Verlegung im Rohr ist jedoch nur zulässig, wenn Vorkehrungen getroffen sind, dass sich im Rohr keine Wasseransammlung bilden kann.

Die Kabel sind halogenfrei, besitzen geringe Rauchgasentwicklung, keine Brandfortleitung und einen Isolationserhalt im Brandfall von 180 Minuten gem. VDE 0472 T. 814. Darüber hinaus hat das Kabel die Prüfung auf Funktionserhalt nach DIN 4102 Teil 12 (E 30) für alle Standard-Tragesysteme (Kabelrinnen und -leitern, Deckenverlegung) bestanden und ist damit für den Einsatz in Brandmeldeanlagen, Anlagen zur Alarmierung und Erteilung von Anweisungen an Personen, Sicherheitsbeleuchtung und sonstige Ersatzstrombeleuchtung gem. VDE 0108 geeignet.

### Normen

nach DIN VDE 0266 VDE 0266:2000-03, DIN 4102-12:1998-11,  
DIN EN IEC 60332-3-24 VDE 0482-332-3-24:2019-05,  
DIN EN 61034-1 VDE 0482-1034-1:2021-02,  
DIN EN 60754-1 VDE 0482-754-1:2021-02

CE = Das Produkt ist konform zur EG-Niederspannungsrichtlinie 2014/35/EU.

### Aufbau

|                            |                                                                                 |
|----------------------------|---------------------------------------------------------------------------------|
| <b>Innenleiter</b>         | Kupferleiter blank ein- oder mehrdrähtig nach VDE 0295:2005-09 Kl. 1 bzw. Kl. 2 |
| <b>Aderisolierung</b>      | halogenfreie Polymermischung                                                    |
| <b>Aderfarbcode</b>        | nach HD 308 S2                                                                  |
| <b>Verseilelement</b>      | Adern gemeinsam verseilt                                                        |
| <b>Außenmantelmaterial</b> | halogenfreie Polymermischung                                                    |

### Application

Security cables are ideal for use everywhere, where in case of fire human life and material assets are to be protected and safety consciousness take a special significance. The cables are suitable for fixed installation in dry and moist rooms, in, above, on and beneath plaster as well as in masonry walls in concrete. These cables are suitable for outdoor applications and in underground by using in conduits or tubes. For installation conduit all precautions must be taken that no accumulation of water can occur in the pipes.

The cables are halogen-free, have low smoke gas development, no fire propagation and insulation retention in the event of fire of 180 minutes in accordance with VDE 0472 Part 814. In addition, the cable has been tested for functional integrity in accordance with DIN 4102 Part 12 (E 30) for all standard carrying systems (Cable troughs and ladders, ceiling installation) and is therefore suitable for use in fire alarm systems, systems for alarming and issuing instructions to people, safety lighting and other backup lighting in accordance with VDE 0108.

### Standards

security cable in the case of fire to DIN VDE 0266 & FE 180:  
Insulation integrity to DIN VDE 0472 part 814 & E 30:  
Function-  
ality to DIN 4102 part 12

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

### Construction

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| <b>Inner Conductor</b>           | bare copper conductor to DIN VDE 0295 cl. 1 or cl. 2, HD 383 |
| <b>Core Insulation</b>           | halogen-free polymer compound                                |
| <b>Core Color</b>                | to DIN VDE 0293-308                                          |
| <b>Stranding Elements</b>        | cores stranded in layers                                     |
| <b>Outer Insulation Material</b> | halogen-free polymer compound                                |

**Techn. Daten**

|                                     |                                |
|-------------------------------------|--------------------------------|
| <b>Nennspannung</b>                 | U <sub>0</sub> /U: 600 /1000 V |
| <b>Nennspannung Gleichstrom DC</b>  | U <sub>0</sub> /U: 0 /0        |
| <b>Prüfspannung</b>                 | 4000 V                         |
| <b>Biegeradius fest (xD)</b>        | 0                              |
| <b>Betriebstemperatur fest</b>      | -5 °C bis 70 °C                |
| <b>Betriebstemperatur beweglich</b> | 0 °C bis 0 °C                  |

**Technical Data**

|                                     |                                |
|-------------------------------------|--------------------------------|
| <b>Nominal Voltage</b>              | U <sub>0</sub> /U: 600 /1000 V |
| <b>Nominal Volatage DC</b>          | U <sub>0</sub> /U: 0 /0        |
| <b>Test Voltage</b>                 | 4000 V                         |
| <b>Bending Radius fixed (xD)</b>    | 0                              |
| <b>Operating Temperature solid</b>  | -5 °C to 70 °C                 |
| <b>Operating Temperature moving</b> | 0 °C to 0 °C                   |

| Art. Nr.<br>Prod. Nr. | Option<br>Option | Abmessung<br>Dimensions | Farbe<br>Color  | Gewicht (kg/km) ca.<br>Weight (kg/km) approx. | Außen-Durchmesser (mm) ca.<br>Outer-Diameter (mm) approx. | Brandlast (kWh/m)<br>Calorific potential (kWh/m) |
|-----------------------|------------------|-------------------------|-----------------|-----------------------------------------------|-----------------------------------------------------------|--------------------------------------------------|
| 02404008              | O                | 1 x 16 re               | orange - orange | 215.0                                         | 9.5                                                       | 0.34                                             |
| 02404009              | O                | 1 x 25 rm               | orange - orange | 305.0                                         | 11.0                                                      | 0.39                                             |
| 02404010              | O                | 1 x 35 rm               | orange - orange | 400.0                                         | 12.0                                                      | 0.45                                             |
| 02404011              | O                | 1 x 50 rm               | orange - orange | 540.0                                         | 13.5                                                      | 0.53                                             |
| 02404012              | O                | 1 x 70 rm               | orange - orange | 750.0                                         | 15.5                                                      | 0.66                                             |
| 02404013              | O                | 1 x 95 rm               | orange - orange | 1,015.0                                       | 17.5                                                      | 0.79                                             |
| 02404084              | J                | 1 x 120 rm              | orange - orange | 1,255.0                                       | 19.0                                                      | 0.91                                             |
| 02404014              | O                | 1 x 120 rm              | orange - orange | 1,255.0                                       | 19.0                                                      | 0.91                                             |
| 02404015              | O                | 1 x 150 rm              | orange - orange | 1,545.0                                       | 21.0                                                      | 1.12                                             |
| 02404016              | O                | 1 x 185 rm              | orange - orange | 1,925.0                                       | 23.0                                                      | 1.34                                             |
| 02404017              | O                | 1 x 240 rm              | orange - orange | 2,450.0                                       | 26.0                                                      | 1.61                                             |
| 02404018              | O                | 2 x 1,5re               | orange - orange | 125.0                                         | 9.5                                                       | 0.34                                             |
| 02404019              | O                | 2 x 2,5re               | orange - orange | 160.0                                         | 10.0                                                      | 0.40                                             |
| 02404020              | O                | 2 x 4re                 | orange - orange | 210.0                                         | 11.0                                                      | 0.47                                             |
| 02404021              | O                | 2 x 6re                 | orange - orange | 280.0                                         | 12.5                                                      | 0.59                                             |
| 02404022              | O                | 2 x 10 re               | orange - orange | 420.0                                         | 15.0                                                      | 0.81                                             |
| 02404075              | O                | 2 x 16 rm               | orange - orange | 630.0                                         | 18.5                                                      | 1.14                                             |
| 02404093              | J                | 3 x 1,5re               | orange - orange | 145.0                                         | 10.0                                                      | 0.37                                             |
| 02404094              | J                | 3 x 2,5re               | orange - orange | 190.0                                         | 10.5                                                      | 0.44                                             |
| 02404096              | J                | 3 x 4re                 | orange - orange | 260.0                                         | 12.0                                                      | 0.55                                             |
| 02404095              | J                | 3 x 6re                 | orange - orange | 340.0                                         | 13.5                                                      | 0.65                                             |
| 02404023              | J                | 3 x 10 re               | orange - orange | 525.0                                         | 16.0                                                      | 0.93                                             |
| 02404109              | J                | 3 x 16 rm               | orange - orange | 785.0                                         | 19.5                                                      | 1.24                                             |
| 02404025              | J                | 3 x 25 rm               | orange - orange | 1,140.0                                       | 23.0                                                      | 1.60                                             |

| Art. Nr.<br>Prod. Nr. | Option<br>Option | Abmessung<br>Dimensions | Farbe<br>Color  | Gewicht (kg/km) ca.<br>Weight (kg/km) approx. | Außen-Durchmesser (mm) ca.<br>Outer-Diameter (mm) approx. | Brandlast (kWh/m)<br>Calorific potential (kWh/m) |
|-----------------------|------------------|-------------------------|-----------------|-----------------------------------------------|-----------------------------------------------------------|--------------------------------------------------|
| 02404030              | J                | 3 x 25/16 rm            | orange - orange | 1,315.0                                       | 24.0                                                      | 1.74                                             |
| 02404026              | J                | 3 x 35 rm               | orange - orange | 1,485.0                                       | 25.0                                                      | 1.88                                             |
| 02404031              | J                | 3 x 35/16 rm            | orange - orange | 1,640.0                                       | 26.0                                                      | 1.99                                             |
| 02404027              | J                | 3 x 50 rm               | orange - orange | 1,970.0                                       | 28.0                                                      | 2.25                                             |
| 02404032              | J                | 3 x 50/25 rm            | orange - orange | 2,230.0                                       | 30.0                                                      | 2.46                                             |
| 02404028              | J                | 3 x 70 rm               | orange - orange | 2,735.0                                       | 32.0                                                      | 2.90                                             |
| 02404033              | J                | 3 x 70/35 rm            | orange - orange | 3,070.0                                       | 34.0                                                      | 3.12                                             |
| 02404034              | J                | 3 x 95/50 rm            | orange - orange | 4,180.0                                       | 39.0                                                      | 3.95                                             |
| 02404035              | J                | 3 x 120/70 rm           | orange - orange | 5,280.0                                       | 43.0                                                      | 4.80                                             |
| 02404036              | J                | 3 x 150/70 rm           | orange - orange | 6,260.0                                       | 47.0                                                      | 5.61                                             |
| 02404037              | J                | 3 x 185/95 rm           | orange - orange | 7,925.0                                       | 52.0                                                      | 6.99                                             |
| 02404038              | J                | 3 x 240/120 rm          | orange - orange | 10,030.0                                      | 58.0                                                      | 8.49                                             |
| 02404099              | J                | 4 x 1,5re               | orange - orange | 170.0                                         | 11.0                                                      | 0.43                                             |
| 02404089              | J                | 4 x 2,5re               | orange - orange | 225.0                                         | 11.5                                                      | 0.51                                             |
| 02404040              | J                | 4 x 4re                 | orange - orange | 315.0                                         | 13.0                                                      | 0.64                                             |
| 02404041              | J                | 4 x 6re                 | orange - orange | 435.0                                         | 15.0                                                      | 0.82                                             |
| 02404042              | J                | 4 x 10 re               | orange - orange | 665.0                                         | 17.5                                                      | 1.16                                             |
| 02404091              | J                | 4 x 16 rm               |                 | 995.0                                         | 22.0                                                      | 1.50                                             |
| 02404044              | J                | 4 x 25 rm               | orange - orange | 1,430.0                                       | 25.0                                                      | 1.88                                             |
| 02404045              | J                | 4 x 35 rm               | orange - orange | 1,680.0                                       | 28.0                                                      | 2.20                                             |
| 02404046              | J                | 4 x 50 rm               | orange - orange | 2,505.0                                       | 31.0                                                      | 2.73                                             |
| 02404047              | J                | 4 x 70 rm               | orange - orange | 3,480.0                                       | 36.0                                                      | 3.50                                             |
| 02404048              | J                | 4 x 95 rm               | orange - orange | 4,705.0                                       | 41.0                                                      | 4.33                                             |
| 02404049              | J                | 4 x 120 rm              | orange - orange | 5,850.0                                       | 45.0                                                      | 5.25                                             |

| Art. Nr.<br>Prod. Nr. | Option<br>Option | Abmessung<br>Dimensions | Farbe<br>Color  | Gewicht (kg/km) ca.<br>Weight (kg/km) approx. | Außen-Durchmesser (mm) ca.<br>Outer-Diameter (mm) approx. | Brandlast (kWh/m)<br>Calorific potential (kWh/m) |
|-----------------------|------------------|-------------------------|-----------------|-----------------------------------------------|-----------------------------------------------------------|--------------------------------------------------|
| 02404050              | J                | 4 x 150 rm              | orange - orange | 7,160.0                                       | 49.0                                                      | 6.35                                             |
| 02404078              | J                | 4 x 240 rm              | orange - orange | 11,380.0                                      | 62.0                                                      | 9.62                                             |
| 02404102              | J                | 5 x 1,5re               | orange - orange | 200.0                                         | 11.5                                                      | 0.50                                             |
| 02404103              | J                | 5 x 2,5re               | orange - orange | 270.0                                         | 12.5                                                      | 0.62                                             |
| 02404053              | J                | 5 x 4re                 | orange - orange | 380.0                                         | 14.0                                                      | 0.77                                             |
| 02404105              | J                | 5 x 6re                 | orange - orange | 520.0                                         | 16.0                                                      | 0.98                                             |
| 02404055              | J                | 5 x 10 re               | orange - orange | 810.0                                         | 19.5                                                      | 1.39                                             |
| 02404056              | J                | 5 x 16 re               | orange - orange | 1,300.0                                       | 24.0                                                      |                                                  |
| 02404057              | J                | 5 x 25 rm               | orange - orange | 1,725.0                                       | 27.0                                                      | 2.21                                             |
| 02404083              | J                | 5 x 35 rm               | orange - orange | 2,270.0                                       | 30.0                                                      | 2.64                                             |
| 02404085              | J                | 5 x 50 rm               | orange - orange | 3,075.0                                       | 34.0                                                      | 3.35                                             |
| 02404088              | J                | 5 x 70 rm               | orange - orange | 4,315.0                                       | 40.0                                                      | 4.37                                             |
| 02404086              | J                | 5 x 95 rm               | orange - orange | 5,815.0                                       | 45.0                                                      | 5.41                                             |
| 02404004              | J                | 7 x 1,5re               | orange - orange | 250.0                                         | 12.5                                                      | 0.59                                             |
| 02404064              | J                | 7 x 2,5re               | orange - orange | 340.0                                         | 14.0                                                      | 0.72                                             |
| 02404071              | J                | 7 x 4 re                | orange - orange | 485.0                                         | 15.5                                                      | 0.99                                             |
| 02404058              | J                | 10 x 1,5re              | orange - orange | 370.0                                         | 16.0                                                      | 0.88                                             |
| 02404065              | J                | 10 x 2,5re              | orange - orange | 505.0                                         | 18.0                                                      | 1.07                                             |
| 02404059              | J                | 12 x 1,5re              | orange - orange | 415.0                                         | 16.5                                                      | 0.96                                             |
| 02404066              | J                | 12 x 2,5re              | orange - orange | 565.0                                         | 18.5                                                      | 1.16                                             |
| 02404061              | J                | 19 x 1,5re              | orange - orange | 600.0                                         | 19.5                                                      | 1.37                                             |
| 02404068              | J                | 19 x 2,5re              | orange - orange | 830.0                                         | 22.0                                                      | 1.67                                             |
| 02404062              | J                | 24 x 1,5re              | orange - orange | 760.0                                         | 23.0                                                      | 1.76                                             |
| 02404063              | J                | 30 x 1,5re              | orange - orange | 940.0                                         | 25.0                                                      | 2.14                                             |