

LSZ-XY



prihláška

Ako spojovacia linka v reproduktorových systémoch.

Materiály používané pri výrobe neobsahujú silikón a kadmia a neobsahujú látky, ktoré narúšajú zmáčanie farby.

štandardy

podľa výrobných noriem,
samohasiaci a spomaľovač horenia EN 60332-1-2, IEC
60332-1

nastavenia

vnútorný vodič Holý medený vodič, jemne vláknový v súlade
s DIN
VDE 0295 trieda 5/IEC 60228 trieda 5

izolácia jadra polyvinylchlorid (PVC)

Vnútorný prvok Paralelné jadrá

Techn. dáta

menovité napätie	U ₀ /U: 200 /300 V
Menovité napätie DC DC	U ₀ /U: 0 /0
Skúšobné napätie	2000 V
Pevný polomer ohybu (xD)	0
Pevná prevádzková teplota	0 °C bis 0 °C
Prevádzková teplota pohyblivá	-5 °C bis 70 °C

Application

As connecting cable in speaker systems.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

acc. to factory standard,
self-extinguishing and flame retardant acc. to DIN EN
60332-1-2, IEC 60332-1

Construction

Inner Conductor bare copper fine wire, or extrafine wire
acc. to DIN VDE 0295

Core Insulation special polyvinylchlorid compound
(PVC)

Stranding Elements cores parallel

Technical Data

Nominal Voltage	U ₀ /U: 200 /300 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	2000 V
Bending Radius fixed (xD)	0
Operating Temperature solid	0 °C to 0 °C
Operating Temperature moving	-5 °C to 70 °C

Art. č. Prod. Nr.	voľba Option	rozmer Dimensions	maľovať Color	hmotnosť (kg/km) Weight (kg/km) approx.	Vonkajší priemer (mm) Outer-Diameter (mm) approx.
00307034		2 x 0,35	black/red - black/red	18.0	
00307025		2 x 0,5	black/red - black/red	22.0	
00307024		2 x 0,5	transparentne - transparent	22.0	
00307001		2 x 0,75	black/red - black/red	26.0	
00307002		2 x 0,75	transparentne - transparent	26.0	
00307013		2 x 1	black/yellow - black/yellow	34.0	
00307010		2 x 1,5	čierna/modrá - black/blue	41.0	
00307020		2 x 1,5	transparent/red - transparent/red	41.0	
00307011		2 x 2,5	black/red - black/red	60.0	
00307005		2 x 2,5	transparent/red - transparent/red	60.0	
00307026		2 x 2,5	black/yellow - black/yellow	60.0	
00307012		2 x 4	black/red - black/red	80.0	
00307031		2 x 4	transparentne - transparent	80.0	
00307008	HF	2 x 10	transparentne - transparent	250.0	
00307017		2 x 10	transparentne - transparent	250.0	