

YSLYCY-JB



prihláška

Pre stredné mechanické namáhanie pre flexibilné použitie s voľným pohybom bez napätia v ťahu a bez núteného riadenia pohybu v suchých, vlhkých a vlhkých miestnostiach, ale nie vonku, ako riadiaca linka v riadiacej a regulačnej technike, v strojárstve, v počítačových systémoch, v vykurovacej a klimatizačnej technike, v strojárstve a ako signálna linka v elektronike. Vysoká hustota tienenia zaisťuje bezinterferenčný prenos signálov a impulzov. Ideálny riadiaci kábel chránený pred rušením pre vyššie uvedené aplikácie.

Materiály používané pri výrobe neobsahujú silikón a kadmia a neobsahujú látky, ktoré narušajú zmáčanie farby.

štandardy

na základe DIN VDE 0245, 0285-525-2-31

CE = Produkt je v súlade so smernicou ES o nízkom napätí 2014/35/EÚ.

nastavenia

vnútorný vodič	Holý medený vodič, jemne vláknový v súlade s DIN VDE 0295 trieda 5/IEC 60228 trieda 5
izolácia jadra	polyvinylchlorid (PVC)
Základný farebný kód	Farebné na HD 308 S2
Vnútorný prvok	Žily uviaznuté vo vrstvách s optimálnou dĺžkou
Materiál vnútornej bundy	polyvinylchlorid (PVC)
Celkové tienenie	medený oplet, pocínovaný
materiál vonkajšieho plášťa	Polyvinylchlorid (PVC) priehľadný
Odolný voči	prevažne odolný voči oleju

Application

For use as a data cable in control circuits, in tool-making and machine industries as well as a signal cable in computer systems and electronics. The more usual PVC inner sheath has been replaced in these cables by a stabilising foil separator, thus reducing the total diameter of the cables considerably and thereby reducing the bending radius, total weight etc. The high covering percentage of the copper screening offers interference-free signal transfer etc. The dense screening assures disturbance-free transmission of all signals and impulses. An ideal disturbance-free control cable for the above application.

The materials used are free from silicon and cadmium and free from varnish damaging substances.

Standards

adapted to DIN VDE 0245, 0285-525-2-31, self-extinguishing and flame retardant acc. to VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1

CE = The product is conformed with the EC Low-Voltage Directive 2014/35/EU.

Construction

Inner Conductor	fine-stranded bare copper acc. DIN VDE 0295 cl. 5 / IEC 60228 cl. 5
Core Insulation	polyvinylchlorid compound (PVC)
Core Color	acc. to HD 308 S2
Stranding Elements	cores stranded in layers with optimal layer-length
Inner Sheath Material	Polyvinylchlorid (PVC)
Overall Shielding	braid shield copper tinned
Outer Insulation Material	special PVC transparent
Constant Against	extensively oil resistant

Techn. dáta

menovité napätie	U ₀ /U: 300 /500 V
Menovité napätie DC DC	U ₀ /U: 0 /0
Skúšobné napätie	2500 V
Polomer ohybu bew. (xD)	10
Pevný polomer ohybu (xD)	0
Pevná prevádzková teplota	-40 °C bis 70 °C
Prevádzková teplota pohyblivá	-5 °C bis 70 °C
Triedy požiaru	Eca

Technical Data

Nominal Voltage	U ₀ /U: 300 /500 V
Nominal Volatage DC	U ₀ /U: 0 /0
Test Voltage	2500 V
Bending Radius moved (xD)	10
Bending Radius fixed (xD)	0
Operating Temperature solid	-40 °C to 70 °C
Operating Temperature moving	-5 °C to 70 °C
Fire Classes	Eca

Art. č. Prod. Nr.	voľba Option	rozmer Dimensions	maľovať Color	hmotnosť (kg/km) Weight (kg/km) approx.	Vonkajší priemer (mm) Outer-Diameter (mm) approx.
00905053	JB	3 x 1,5	transparentne - transparent	172.0	10.5
00927136	JB	3 x 2,5	šedá - grey	230.0	11.5
00905039	JB	3 x 2,5	transparentne - transparent	230.0	11.5
00905063	JB	4 x 1,5	transparentne - transparent	197.0	10.8
00905074	JB	4 x 2,5	transparentne - transparent	300.0	13.1
00905080	JB	4 x 4	transparentne - transparent	410.0	14.0
00905059	JB	4 x 6	transparentne - transparent	560.0	15.6
00905141	JB	4 x 10	šedá - grey	920.0	21.2
00905060	JB	4 x 10	transparentne - transparent	920.0	21.2
00905081	JB	4 x 16	transparentne - transparent	1,120.0	24.0
00927139	JB	4 x 16	šedá - grey	1,120.0	24.0
00905040	JB	4 x 25	šedá - grey	1,994.0	29.0
00905054	JB	4 x 25	transparentne - transparent	1,994.0	29.0
00905046	JB	4 x 35	transparentne - transparent	2,042.0	32.0
00905127	JB	4 x 35	šedá - grey	2,042.0	32.0
00905033	JB	4 x 50	transparentne - transparent	2,822.0	38.0
00905056	JB	4 x 50	šedá - grey	2,822.0	38.0
00905034	JB	4 x 70	transparentne - transparent	3,802.0	44.0
00905140	JB	4 x 70	šedá - grey	3,802.0	44.0
00905035	JB	4 x 95	transparentne - transparent	5,003.0	50.0
00905125	JB	4 x 95	šedá - grey	5,003.0	50.0
00927153	JB	4 x 120	transparentne - transparent	6,200.0	56.0
00905036	JB	4 x 120	šedá - grey	6,200.0	56.0
00905094	JB	4 x 150	transparentne - transparent	9,340.0	63.5

Art. č. Prod. Nr.	voľba Option	rozmer Dimensions	maľovať Color	hmotnosť (kg/km) Weight (kg/km) approx.	Vonkajší priemer (mm) Outer-Diameter (mm) approx.
00905098	JB	4 x 185	transparentne - transparent	11,200.0	68.0
00905049	JB	5 x 2,5	transparentne - transparent	320.0	13.5
00905082	JB	5 x 4	transparentne - transparent	502.0	14.8
00905084	JB	5 x 6	transparentne - transparent	750.0	17.0
00905045	JB	5 x 10	transparentne - transparent	892.0	22.5
00905068	JB	5 x 16	transparentne - transparent	1,325.0	25.2
00905096	JB	5 x 25	transparentne - transparent	2,310.0	31.5
00927142	JB	5 x 35	transparentne - transparent	2,885.0	38.2